

CDMA2000

WCDMA

Bluetooth

GSM

1xEV-DO

Analog

TDMA



R&S®CMU200 Universal Radio Communication Tester

Data sheet

Version
08.01

July
2007


ROHDE & SCHWARZ

CONTENTS

BASE UNIT SPECIFICATIONS	4
TIMEBASE TCXO	4
TIMEBASE OCXO – R&S®CMU-B11 OPTION	4
TIMEBASE OCXO – R&S®CMU-B12 OPTION	4
REFERENCE FREQUENCY INPUTS/OUTPUTS	4
RF GENERATOR	5
RF ANALYZER	6
<i>Power meter (wideband)</i>	7
<i>Power meter (frequency-selective)</i>	7
SPECTRUM ANALYZER	8
GENERAL SPECIFICATIONS	9
INPUTS AND OUTPUTS (REAR PANEL)	10
GSM SPECIFICATIONS – MOBILE STATION TEST	11
RF GENERATOR	11
R&S®CMU-B95 OPTION ADDITIONAL RF GENERATOR	12
R&S®CMU-B96 OPTION ADDITIONAL RF GENERATOR	12
<i>Path 1 for GSM</i>	12
<i>Influence on RF interface</i>	13
RF ANALYZER	13
<i>Power meter (frequency-selective)</i>	13
<i>Modulation analysis</i>	14
<i>Burst power measurement</i>	14
<i>Spectrum due to modulation</i>	15
<i>Spectrum due to switching</i>	15
R&S®CMU-B52 OPTION SPEECH CODEC	15
TDMA SPECIFICATIONS – MOBILE STATION TEST	16
RF GENERATOR	16
RF ANALYZER	16
<i>Modulation analysis</i>	16
<i>Power meter (frequency-selective)</i>	17
<i>Power versus time measurement</i>	17
<i>Adjacent channel power measurement</i>	17
AMPS SPECIFICATIONS – MOBILE STATION TEST	18
RF GENERATOR	18
RF ANALYZER	18
<i>Power meter (frequency-selective)</i>	19
<i>FM measurement</i>	19
AF GENERATOR	19
AF ANALYZER	19
CDMA2000® SPECIFICATIONS – MOBILE STATION TEST	20
RF GENERATOR	20
RF ANALYZER	21
<i>Power meter (frequency-selective)</i>	22
<i>Modulation analyzer</i>	22
R&S®CMU-B85 OPTION SPEECH CODEC	23

1XEV-DO SPECIFICATIONS – ACCESS TERMINAL TEST	24
RF GENERATOR.....	24
RF ANALYZER	26
<i>Power meter (frequency-selective).....</i>	26
<i>Modulation analyzer</i>	27
WCDMA SPECIFICATIONS – MOBILE STATION (UE) TEST.....	28
RF GENERATOR.....	28
R&S®CMU-B96 ADDITIONAL RF GENERATOR OPTION.....	30
<i>Path 2 for WCDMA.....</i>	30
<i>Influence on RF interface</i>	30
RF ANALYZER (TX MEASUREMENTS).....	31
<i>Modulation analysis</i>	32
<i>Spectrum measurements</i>	33
<i>Power meter (frequency-selective).....</i>	34
<i>Code domain power</i>	35
<i>Receiver quality (bit error rate measurements)</i>	35
R&S®CMU-B52 OPTION SPEECH CODEC	36
BLUETOOTH® SPECIFICATIONS	37
RF GENERATOR.....	37
RF ANALYZER	38
<i>Power meter (frequency-selective) and power versus time.....</i>	38
<i>Modulation analyzer</i>	38
<i>Timing measurement.....</i>	39
R&S®CMU-B52 OPTION SPEECH CODEC	39
R&S®CMU-B17 OPTION I/Q/IF INTERFACE	40
I/Q INTERFACE	40
INFLUENCE ON RF INTERFACE	40
IF INTERFACE.....	41
REMARKS	42
<i>Additional information for GSM:.....</i>	42
<i>Aspects to be considered if TX or RX signal paths are interrupted:.....</i>	42
<i>Notes for measuring I/Q/IF signals applied to inputs of the R&S®CMU-B17 option on the R&S®CMU200 RX path:.....</i>	42
R&S®CMU-B41 OPTION AUDIO GENERATOR/ANALYZER	43
AF GENERATOR	43
AF ANALYZER	43
R&S®CMU-U99/B99 OPTION RF1 LEVEL RANGE IDENTICAL TO RF2	43

The specifications for the R&S®CMU200 (Order No. 1100.0008.02/10/30/53) refer to a fully equipped unit with all relevant options installed.

CDMA2000® is a registered trademark of the Telecommunications Industry Association (TIA -USA).

The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Rohde&Schwarz is under license.

Base unit specifications

Timebase TCXO

Max. frequency drift	in temperature range +5 °C to +45 °C	$\pm 1 \times 10^{-6}$
Max. aging		$\pm 1 \times 10^{-6}/\text{year}$

Timebase OCXO – R&S®CMU-B11 option

Max. frequency drift	in temperature range +5 °C to +45 °C	$\pm 1 \times 10^{-7}$
Max. aging	after 30 days of operation	$\pm 2 \times 10^{-7}/\text{year}$ $\pm 5 \times 10^{-9}/\text{day}$
Warmup time	at +25 °C	approx. 5 min

Timebase OCXO – R&S®CMU-B12 option

Max. frequency drift		
	in temperature range +5 °C to +45 °C, referred to +25 °C	$\pm 5 \times 10^{-9}$
	with instrument orientation	$\pm 3 \times 10^{-9}$
	referred to turn-off frequency after 2 h warmup time following a 24 h off time at +25 °C	$\pm 5 \times 10^{-9}$

Max. aging	after 30 days of operation	$\pm 3.5 \times 10^{-8}/\text{year}$ $\pm 5 \times 10^{-10}/\text{day}$
Warmup time	at +25 °C	approx. 10 min

Reference frequency inputs/outputs

Synchronization input		BNC connector REF IN
Frequency	sinewave squarewave (TTL level)	1 MHz to 52 MHz, step 1 kHz 10 kHz to 52 MHz, step 1 kHz
Max. frequency variation		$\pm 5 \times 10^{-6}$
Input voltage range		0.5 V to 2 V, rms
Impedance		50 Ω

Synchronization output 1		BNC connector REF OUT 1
Frequency		10 MHz from internal reference or frequency at synchronization input
Output voltage		>1.4 V, peak-peak
Impedance		50 Ω

Synchronization output 2		BNC connector REF OUT 2
Frequency		net-specific frequencies in range 100 kHz to 40 MHz
Output voltage	f ≤ 13 MHz	>1.0 V, peak-peak
Impedance		50 Ω

RF generator

Frequency range	100 kHz to 2700 MHz	
Frequency resolution	0.1 Hz	
Frequency uncertainty	same as timebase + frequency resolution	
Frequency settling time	<400 µs to $\Delta f < 1$ kHz	

Output level range		
RF 1	100 kHz to 2200 MHz 2200 MHz to 2700 MHz	-130 dBm to -27 dBm -130 dBm to -33 dBm
RF 2	100 kHz to 2200 MHz 2200 MHz to 2700 MHz	-130 dBm to -10 dBm -130 dBm to -16 dBm
RF 3 OUT	100 kHz to 2200 MHz 2200 MHz to 2700 MHz	-90 dBm to +13 dBm -90 dBm to +5 dBm

Output level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	output level ≥ -106 dBm 10 MHz to 450 MHz 450 MHz to 2200 MHz 2200 MHz to 2700 MHz output level > -117 dBm 450 MHz to 2200 MHz 2200 MHz to 2700 MHz output level -117 dBm to -130 dBm 450 MHz to 2200 MHz 2200 MHz to 2700 MHz	<0.6 dB <0.6 dB <0.8 dB <0.6 dB ¹ <0.8 dB ¹ <1.5 dB ^{1, 2} <1.5 dB ^{1, 2}
RF 3 OUT	10 MHz to 450 MHz output level -80 dBm to +10 dBm 450 MHz to 2200 MHz output level -90 dBm to +10 dBm 2200 MHz to 2700 MHz output level -90 dBm to +5 dBm	<0.8 dB <0.8 dB <1.0 dB

Output level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	output level ≥ -106 dBm 10 MHz to 450 MHz 450 MHz to 2200 MHz 2200 MHz to 2700 MHz output level > -117 dBm 450 MHz to 2200 MHz 2200 MHz to 2700 MHz output level -117 dBm to -130 dBm 450 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.0 dB <1.0 dB <1.5 dB <1.0 dB ¹ <1.5 dB ¹ <1.5 dB ^{1, 2} <1.5 dB ^{1, 2}
RF 3 OUT	10 MHz to 450 MHz output level -80 dBm to +10 dBm 450 MHz to 2200 MHz output level -90 dBm to +10 dBm 2200 MHz to 2700 MHz output level -90 dBm to +5 dBm	<1.0 dB <1.0 dB <1.5 dB

Output level settling time	<4 µs
-----------------------------------	-------

Output level resolution	0.1 dB
--------------------------------	--------

¹ Not valid at frequencies of net-clock harmonics.

² Valid for RF1 only.

Generator RF level repeatability	typical values after 1 h warmup time output level ≥ -80 dBm output level < -80 dBm	<0.01 dB <0.1 dB
VSWR		
RF 1	10 MHz to 2000 MHz 2000 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.2 <1.3 <1.6
RF 2	10 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.2 <1.6
RF 3 OUT	10 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.5 <1.7

Attenuation of harmonics	up to 7 GHz	
RF 1, RF 2	$f_0 = 10$ MHz to 200 MHz	>20 dB
RF 1, RF 2	$f_0 = 200$ MHz to 2200 MHz	>30 dB
RF 3 OUT	$f_0 = 10$ MHz to 2200 MHz output level $\leq +10$ dBm	>20 dB

Attenuation of nonharmonics	10 MHz to 2200 MHz, at $f > 5$ kHz from carrier	>40 dB
------------------------------------	--	--------

Phase noise	single sideband, $f < 2.2$ GHz	
Carrier offset	20 kHz to 250 kHz ≥ 250 kHz	<-100 dBc, 1 Hz <-110 dBc, 1 Hz

Residual FM	$f < 2.2$ GHz 30 Hz to 15 kHz ITU-T (formerly CCITT)	<50 Hz, rms, <200 Hz, peak <5 Hz, rms
--------------------	--	--

Residual AM	$f < 2.2$ GHz ITU-T (formerly CCITT)	<0.02%, rms
--------------------	---	-------------

I/Q modulation		
Carrier suppression	data for frequency offset range 0 Hz to ± 135 kHz	>40 dB

FM modulation		
Deviation range		10 kHz to 440 kHz
Deviation resolution		1 Hz
Modulation frequency range		100 Hz to 50 kHz
Modulation distortion	modulation frequency 1 kHz, deviation 80 kHz	<2 %
Deviation uncertainty		<5 % + resolution + residual FM

RF analyzer

VSWR		
RF 1	10 MHz to 2000 MHz 2000 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.2 <1.3 <1.6
RF 2	10 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.2 <1.6
RF 4 IN	10 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.5 <1.6

Inherent spurious response	<i>RF Attenuation → Low Distortion,</i> 20 MHz to 2200 MHz, except 1816.115 MHz	<-50 dB
-----------------------------------	---	---------

Inherent harmonics	$f_{in} = 50 \text{ MHz to } 1100 \text{ MHz}$, $f_{selected} = 100 \text{ MHz to } 2200 \text{ MHz}$	
RF 1, RF 2		<-30 dB
RF 4 IN		<-20 dB

Phase noise	single sideband, $f < 2.2 \text{ GHz}$	
Carrier offset	20 kHz to 250 kHz 250 kHz to 400 kHz $\geq 400 \text{ kHz}$	<-100 dBc, 1 Hz <-110 dBc, 1 Hz <-118 dBc, 1 Hz

Residual FM	$f < 2.2 \text{ GHz}$ 30 Hz to 15 kHz ITU-T (formerly CCITT)	<50 Hz, rms, <200 Hz, peak <5 Hz, rms
--------------------	--	--

Residual AM	$f < 2.2 \text{ GHz}$ ITU-T (formerly CCITT)	<0.02%, rms
--------------------	---	-------------

Power meter (wideband)

Frequency range	100 kHz to 2700 MHz
------------------------	---------------------

Level range		
RF 1	continuous power ³	
	100 kHz to 2200 MHz	+6 dBm to +47 dBm (50 W)
	2200 MHz to 2700 MHz	+10 dBm to +47 dBm (50 W)
	peak envelope power ⁴ (PEP)	+53 dBm (200 W)
RF 2	continuous power	
	100 kHz to 2200 MHz	-8 dBm to +33 dBm (2 W)
	2200 MHz to 2700 MHz	-4 dBm to +33 dBm (2 W)
	peak envelope power ⁴ (PEP)	+39 dBm (8 W)
RF 4 IN	continuous power and PEP	
	100 kHz to 2200 MHz	-33 dBm to 0 dBm
	2200 MHz to 2700 MHz	-29 dBm to 0 dBm

Level uncertainty		
RF 1	input level +10 dBm to +20 dBm	
	50 MHz to 2700 MHz	<1.0 dB ⁵
	input level +20 dBm to +47 dBm	
	50 MHz to 2700 MHz	<0.5 dB ^{5, 6}
RF 2	input level -4 dBm to +6 dBm	
	50 MHz to 2700 MHz	<1.0 dB ⁵
	input level +6 dBm to +33 dBm	
	50 MHz to 2700 MHz	<0.5 dB ⁵
RF 4 IN	input level -29 dBm to -19 dBm	
	50 MHz to 2700 MHz	<1.5 dB
	input level -19 dBm to 0 dBm	
	50 MHz to 2700 MHz	<0.8 dB

Level resolution	in manual mode	0.1 dB
	in remote control mode	0.01 dB

Power meter (frequency-selective)

Frequency range	10 MHz to 2700 MHz
------------------------	--------------------

Frequency resolution	0.1 Hz
-----------------------------	--------

³ 50 W in temperature range +5 °C to +30 °C, linear degradation down to 25 W at +45 °C.

⁴ Mean value of power versus time must be equal to or less than allowed continuous power.

⁵ Temperature range +5 °C to +20 °C or +35 °C to +45 °C and f > 2200 MHz: add 0.2 dB.

⁶ Calibrated for input level >+33 dBm only in frequency range 800 MHz to 2000 MHz.

Resolution bandwidths		10 Hz to 1 MHz in 1/2/3/5 steps
------------------------------	--	---------------------------------

Level range		
RF 1	continuous power ³ 10 MHz to 2200 MHz 2200 MHz to 2700 MHz peak envelope power ⁴ (PEP)	-40 dBm to +47 dBm (50 W) -34 dBm to +47 dBm (50 W) +53 dBm (200 W)
RF 2	continuous power 10 MHz to 2200 MHz 2200 MHz to 2700 MHz peak envelope power ⁴ (PEP)	-54 dBm to +33 dBm (2 W) -48 dBm to +33 dBm (2 W) +39 dBm (8 W)
RF 4 IN	continuous power and PEP 10 MHz to 2200 MHz 2200 MHz to 2700 MHz	-80 dBm to 0 dBm -74 dBm to 0 dBm

Level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<0.5 dB <0.7 dB
RF 4 IN	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<0.7 dB <0.9 dB

Level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.0 dB <1.0 dB
RF 4 IN	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.0 dB <1.1 dB

Level resolution	in manual mode in remote control mode	0.1 dB 0.01 dB
-------------------------	--	-------------------

RF level measurement repeatability	typical values after 1 h warmup input level ≥ -40 dBm input level < -40 dBm	<0.01 dB <0.03 dB
---	---	----------------------

Spectrum analyzer

Frequency range		10 MHz to 2.7 GHz
Span		zero span to full span
Frequency resolution		0.1 Hz
Resolution bandwidths		10 Hz to 1 MHz in 1/2/3/5 steps
Sweep time	depending on resolution bandwidth (RBW)	≥100 ms
Display		560 dots, horizontal
Marker		up to 3, absolute/relative
Display line		1
Display scale		10/20/30/50/80/100 dB

Level range		
RF 1	continuous power ³ peak envelope power ⁴ (PEP)	up to +47 dBm (50 W) up to +53 dBm (200 W)
RF 2	continuous power peak envelope power ⁴ (PEP)	up to +33 dBm (2 W) up to +39 dBm (8 W)
RF 4 IN	continuous power and PEP	up to 0 dBm

Level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<0.5 dB <0.7 dB
RF 4 IN	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<0.7 dB <0.9 dB

Level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.0 dB <1.0 dB
RF 4 IN	50 MHz to 2200 MHz 2200 MHz to 2700 MHz	<1.0 dB <1.1 dB

Reference level for full dynamic range	<i>RF Attenuation → Low Noise,</i> logarithmic level display	
RF 1		+10 dBm to +47 dBm
RF 2		-4 dBm to +33 dBm
RF 4 IN		-22 dBm to 0 dBm

Displayed average noise level	<i>RF Attenuation → Low Noise,</i> RBW → 1 kHz, 10 MHz to 2200 MHz 2200 MHz to 2700 MHz	<-100 dBc <-95 dBc
--------------------------------------	--	-----------------------

Inherent spurious response	<i>RF Attenuation → Low Distortion,</i> 20 MHz to 2200 MHz, except 1816.115 MHz	<-50 dB
-----------------------------------	---	---------

Inherent harmonics	$f_{in} = 50 \text{ MHz to } 1100 \text{ MHz}$, $f_{selected} = 100 \text{ MHz to } 2200 \text{ MHz}$	
RF 1, RF 2		<-30 dB
RF 4 IN		<-20 dB

General specifications

Operating temperature range		+5 °C to +45 °C, in line with EN60068-2-1 and -2
Storage temperature range		-25 °C to +60 °C, in line with EN60068-2-1 and -2
Humidity	+40 °C, non-condensing	80 % relative humidity, in line with EN 60068-2-3

Electromagnetic compatibility		in line with EMC Directive 89/336/EEC, applied standard: EN 61326 (immunity for industrial environment; class B emissions)
--------------------------------------	--	---

Electrical safety		IEC 61010-1, EN 61010-1, UL3111-1, CAN/CSA-C22.2 No. 1010.1
--------------------------	--	--

Mechanical resistance	non-operating mode	
Vibration	sinusoidal	in line with EN 60068-2-6, EN 61010-1, MIL-T-28800 D class 5, 5 Hz to 150 Hz, max. 2 g at 55 Hz, 55 Hz to 150 Hz, 0.5 g const
Vibration	random	in line with EN 60068-2-64 10 Hz to 300 Hz, acceleration 1.2 g rms
Shock		in line with EN 60068-2-27, MIL-STD-810D 40 g shock spectrum

Power supply		power factor correction, in line with EN61000-3-2
Input		100 V to 240 V ±10 % (AC), max. 500 VA, 50 Hz to 400 Hz -5 % to +10 %
Power consumption	base unit with typical options	approx. 130 W approx. 180 W

Display	21 cm TFT color display (8.4")	
Resolution	640 × 480 pixels (VGA resolution)	
Pixel failure rate	<2 × 10 ⁻⁵	

Dimensions	W × H × D, overall	465.1 mm × 197.3 mm × 517.0 mm 18.31 in × 7.77 in × 20.35 in (19" 1/1, 4 HU, 450)
-------------------	--------------------	---

Weight	base unit	approx. 14 kg approx. 30.86 lb
	with typical options	approx. 18 kg approx. 39.68 lb

Inputs and outputs (rear panel)

IF 3 RX CH1	BNC female	
Frequency	WCDMA other networks/RF	7.68 MHz 10.7 MHz
Max. output level		0 dBm
Impedance		50 Ω

Remote control interfaces		
IEC/IEEE bus	IEC 60625-2 (IEEE 488.2)	24-pin Amphenol connector
Serial interface COM 1, COM 2	RS-232-C (COM)	9-pin D-Sub connector

Printer interface LPT	parallel (Centronics compatible)	25-pin D-Sub connector
------------------------------	----------------------------------	------------------------

Keyboard	PS/2 connector	
-----------------	----------------	--

External monitor (VGA)	15-pin D-Sub connector	
-------------------------------	------------------------	--

GSM specifications – mobile station test

RF generator

Modulation	GMSK, $B \times T = 0.3$ 8PSK	
Frequency range	GSM400 band	460 MHz to 468 MHz 488 MHz to 496 MHz
	GSM850 band	869 MHz to 894 MHz
	GSM900 band	921 MHz to 960 MHz
	GSM1800 band	1805 MHz to 1880 MHz
	GSM1900 band	1930 MHz to 1990 MHz
Attenuation of inband spurious emissions	>50 dB	
Inherent phase error	GMSK	<1°, rms <4°, peak
Inherent EVM	8PSK	<2 %, rms
Frequency settling time	to residual phase of 4°	
<500 µs		
Output level range	GMSK	
RF 1	−130 dBm to −27 dBm	
RF 2	−130 dBm to −10 dBm	
RF 3 OUT	−90 dBm to +13 dBm	
Output level range	8PSK	
RF 1	−130 dBm to −31 dBm	
RF 2	−130 dBm to −14 dBm	
RF 3 OUT	−90 dBm to +9 dBm	
Output level resolution	0.1 dB	
Output level uncertainty	in temperature range +20 °C to 35 °C	
RF 1, RF 2	output level >−117 dBm	<0.5 dB
RF 3 OUT	−90 dBm to +10 dBm (GMSK) −90 dBm to +6 dBm (8PSK)	<0.7 dB <0.7 dB
Output level uncertainty	in temperature range +5 °C to 45 °C	
RF 1, RF 2	output level >−117 dBm	<0.7 dB
RF 3 OUT	−90 dBm to +10 dBm (GMSK) −90 dBm to +6 dBm (8PSK)	<0.9 dB <0.9 dB

R&S®CMU-B95 option additional RF generator

Modulation		GMSK, B × T = 0.3 8PSK
Frequency range		
	GSM400 band	460 MHz to 468 MHz 488 MHz to 496 MHz
	GSM850 band	869 MHz to 894 MHz
	GSM900 band	921 MHz to 960 MHz
	GSM1800 band	1805 MHz to 1880 MHz
	GSM1900 band	1930 MHz to 1990 MHz
Frequency resolution		200 kHz
Frequency uncertainty		same as time base, see base unit specifications
Inherent phase error	GMSK	<5°, rms
Output level range	GMSK	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-122 dBm to -72 dBm -110 dBm to -60 dBm
RF 2		-110 dBm to -60 dBm
Output level range	8PSK	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-122 dBm to -76 dBm -110 dBm to -64 dBm
RF 2		-110 dBm to -64 dBm
Output level resolution		1 dB
Reduced input level range	if R&S®CMU-B95 is installed	
RF 1	continuous input power	max. 2 W

R&S®CMU-B96 option additional RF generator

Path 1 for GSM

Modulation		GMSK, B × T = 0.3 8PSK
Frequency range		
	GSM400 band	460 MHz to 468 MHz 488 MHz to 496 MHz
	GSM850 band	869 MHz to 894 MHz
	GSM900 band	921 MHz to 960 MHz
	GSM1800 band	1805 MHz to 1880 MHz
	GSM1900 band	1930 MHz to 1990 MHz
Frequency resolution		2.5 kHz
Frequency uncertainty		same as time base, see base unit specifications
Inherent phase error	GMSK	<5°, rms

Output level range	GMSK	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-115 dBm to -72 dBm -103 dBm to -60 dBm
RF 2		-103 dBm to -60 dBm

Output level range	8PSK	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-115 dBm to -76 dBm -103 dBm to -64 dBm
RF 2		-103 dBm to -64 dBm

Output level range	GMSK overrange mode	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-110 dBm to -28 dBm -90 dBm to -14 dBm
RF 2		-90 dBm to -14 dBm
RF 3 OUT		-70 dBm to +9 dBm

Output level range	8PSK overrange mode	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-110 dBm to -32 dBm -90 dBm to -18 dBm
RF 2		-90 dBm to -18 dBm
RF 3 OUT		-70 dBm to +5 dBm

Output level resolution	1 dB
--------------------------------	------

Influence on RF interface

Reduced input level range	if R&S®CMU-B96 is installed	
RF 1	continuous input power	max. 2 W

RF level uncertainty	usage of R&S®CMU-B96 in overrange mode may influence all RF signal levels and their quality	
-----------------------------	---	--

RF analyzer

Frequency range		
	GSM400 band	450 MHz to 458 MHz 478 MHz to 486 MHz
	GSM850 band	824 MHz to 849 MHz
	GSM900 band	876 MHz to 915 MHz
	GSM1800 band	1710 MHz to 1785 MHz
	GSM1900 band	1850 MHz to 1910 MHz

Power meter (frequency-selective)

Level range		
RF 1	continuous power ³	-40 dBm to +47 dBm (50 W)
	peak envelope power ⁴ (PEP)	+53 dBm (200 W)
RF 2	continuous power	-54 dBm to +33 dBm (2 W)
	peak envelope power ⁴ (PEP)	+39 dBm (8 W)
RF 4 IN	continuous power and PEP	-80 dBm to 0 dBm

Level uncertainty	in temperature range +20 °C to +35 °C	<0.5 dB
	in temperature range +5 °C to +45 °C	<0.7 dB

Level resolution	in manual mode	0.1 dB
	in remote control mode	0.01 dB

Measurement bandwidth	selectable	500 kHz or 600 kHz
------------------------------	------------	--------------------

Modulation analysis

Level range	peak envelope power (PEP)	
RF 1	see footnote ⁴	-6 dBm to +53 dBm
RF 2	see footnote ⁴	-20 dBm to +39 dBm
RF 4 IN		-60 dBm to 0 dBm

Inherent phase error	GMSK	<0.6°, rms <2°, peak
-----------------------------	------	-------------------------

Inherent EVM	8PSK	≤1.0 %, rms
---------------------	------	-------------

Frequency measurement uncertainty		≤10 Hz + drift of time base, see base unit specifications
--	--	--

Measurement bandwidth	selectable	500 kHz or 600 kHz
------------------------------	------------	--------------------

Burst power measurement

Reference level for full dynamic range	GMSK, <i>RF Attenuation → Low Noise</i>	
RF 1	see footnote ⁴	+10 dBm to +53 dBm
RF 2	see footnote ⁴	-4 dBm to +39 dBm
RF 4 IN		-22 dBm to 0 dBm

Reference level for full dynamic range	8PSK, <i>RF Attenuation → Low Noise</i>	
RF 1	see footnote ⁴	+6 dBm to +49 dBm
RF 2	see footnote ⁴	-8 dBm to +35 dBm
RF 4 IN		-26 dBm to -4 dBm

Dynamic range	Filter → 500 kHz, rms, <i>RF Attenuation → Low Noise</i>	
	GMSK	>72 dB
	8PSK	>69 dB

Relative measurement uncertainty		
	result > -40 dB	<0.1 dB
	-60 dB ≤ result ≤ -40 dB	<0.5 dB

Resolution	in active part of burst	0.1 dB
-------------------	-------------------------	--------

Measurement bandwidth	selectable	500 kHz or 600 kHz
------------------------------	------------	--------------------

Spectrum due to modulation

Reference level for full dynamic range	GMSK, RF Attenuation → Low Noise	
RF 1		+10 dBm to +47 dBm
RF 2		-4 dBm to +33 dBm
RF 4 IN		-22 dBm to 0 dBm

Test method	relative measurement, averaging
--------------------	---------------------------------

Filter bandwidth	30 kHz resolution filter, 5 pole
-------------------------	----------------------------------

Measurement	at an offset of	100, 200, 250, 400, 600, 800, 1000, 1200, 1400, 1600, 1800 kHz
--------------------	-----------------	--

Dynamic range	with offset ≥1200 kHz	>74 dB
----------------------	-----------------------	--------

Spectrum due to switching

Reference level for full dynamic range	GMSK, RF Attenuation → Low Noise	
RF 1		+10 dBm to +47 dBm
RF 2		-4 dBm to +33 dBm
RF 4 IN		-22 dBm to 0 dBm

Test method	absolute measurement, max. hold over several measurements
--------------------	---

Filter bandwidth	30 kHz resolution filter, 5 pole
-------------------------	----------------------------------

Measurement	at an offset of	400, 600, 800, 1200, 1800 kHz
--------------------	-----------------	-------------------------------

Dynamic range	with offset ≥1200 kHz	>72 dB
----------------------	-----------------------	--------

R&S®CMU-B52 option speech codec

Speech decoder output	SPEECH HANDSET OUT	9-pin D-Sub connector
Output impedance		<10 Ω
Maximum output current		20 mA, peak
Full-range output level		1 V, peak

Speech coder input	SPEECH HANDSET IN	9-pin D-Sub connector
Input impedance		100 kΩ
Full-range input level	low sensitivity high sensitivity	1.4 V, peak 0.1 V, peak

TDMA specifications – mobile station test

RF generator

Frequency range	signaling mode	
	US Cellular	869 MHz to 894 MHz
	PCS (US)	1930 MHz to 1990 MHz
Frequency range	non-signaling mode	10 MHz to 2200 MHz
Frequency resolution	non-signaling mode	1 Hz
Frequency uncertainty		same as time base, see base unit specifications
Output level range		
RF 1		-130 dBm to -32 dBm
RF 2		-130 dBm to -15 dBm
RF 3 OUT		-90 dBm to +8 dBm
Output level resolution		0.1 dB
Output level uncertainty		see base unit specifications
Modulation	$\pi/4$ DQPSK or unmodulated (non-signaling mode)	
Uncertainty	EVM	<2.5 %, rms
Carrier suppression		>40 dB

RF analyzer

Frequency range	signaling mode	
	US Cellular	824 MHz to 849 MHz
	PCS (US)	1850 MHz to 1910 MHz
Frequency range	non-signaling mode	10 MHz to 2200 MHz
Frequency resolution	non-signaling mode	1 Hz
Frequency uncertainty		same as time base, see base unit specifications

Modulation analysis

Frequency range	signaling mode	
	US Cellular	824 MHz to 849 MHz
	PCS (US)	1850 MHz to 1910 MHz
EVM		
	residual	<2.0 %, rms
	residual	<4 %, peak
I/Q offset	residual	<-50 dB (0.3%)
I/Q imbalance	residual	<-50 dB (0.3%)

Frequency measurement range	-2 kHz to +2 kHz
------------------------------------	------------------

Frequency measurement uncertainty	≤5 Hz + drift of time base, see base unit specifications
--	---

Power meter (frequency-selective)

Level range	see base unit specifications
--------------------	------------------------------

Level uncertainty	see base unit specifications
--------------------------	------------------------------

Power versus time measurement

Reference level for full dynamic range		
RF 1		+4 dBm to +47 dBm
RF 2		-10 dBm to +33 dBm
RF 4 IN		-28 dBm to -6 dBm

Dynamic range	<i>Filter → 100 kHz, rms, RF Attenuation → Low Noise</i>	>74 dB
----------------------	--	--------

Relative measurement uncertainty		
	result > -40 dB	<0.1 dB
	-60 dB ≤ result ≤ -40 dB	<0.5 dB

Residual leakage power level		<-65 dBm
-------------------------------------	--	----------

Adjacent channel power measurement

Dynamic range		
	first adjacent channel	>45 dB
	second and third adjacent channel	>55 dB

AMPS specifications – mobile station test

RF generator

Frequency range	signaling mode	
	US Cellular	869 MHz to 894 MHz
Frequency range	non-signaling mode	10 MHz to 2200 MHz
Frequency resolution	non-signaling mode	1 Hz
Frequency uncertainty		same as time base, see base unit specifications
Output level range		
RF 1		-130 dBm to -27 dBm
RF 2		-130 dBm to -10 dBm
RF 3 OUT		-99 dBm to +13 dBm
Output level resolution		0.1 dB
Output level uncertainty		see base unit specifications and add 0.1 dB
FM modulation		
Deviation range		100 Hz to 20 kHz
Deviation resolution		1 Hz
Modulation frequency range		100 Hz to 15.999 kHz
Modulation distortion	SINAD, modulation frequency 1 kHz, deviation 8 kHz, BW 30 Hz to 15 kHz	≥40 dB
Residual FM	BW 300 Hz to 3 kHz	<10 Hz, rms
Deviation uncertainty	modulation frequency 1 kHz, deviation 8 kHz, BW 30 Hz to 15 kHz	<2 % of setting + residual FM
Deviation frequency response	modulation frequency 300 Hz to 15.999 kHz	≤1 dB

RF analyzer

Frequency range	signaling mode	
	US Cellular	824 MHz to 849 MHz
Frequency range	non-signaling mode	10 MHz to 2200 MHz
Frequency resolution	non-signaling mode	1 Hz
Frequency uncertainty		same as time base, see base unit specifications

Power meter (frequency-selective)

Max. level range		
RF 1		0 dBm to +53 dBm
RF 2		-14 dBm to +39 dBm
RF 4 IN		-37 dBm to +0 dBm

Level uncertainty	see base unit specifications
--------------------------	------------------------------

Level resolution	0.1 dB
-------------------------	--------

FM measurement

Dynamic range	30 dB below max. level
----------------------	------------------------

RF bandwidth	2 × deviation + 4 × modulation frequency	136 kHz
---------------------	--	---------

Deviation range	0 Hz to 47 kHz
------------------------	----------------

Resolution	1 Hz
-------------------	------

Modulation frequency range	100 Hz to 18 kHz
-----------------------------------	------------------

Residual FM		
	BW 300 Hz to 3 kHz	<5 Hz, rms
	BW 6 Hz to 20 kHz	<18 Hz, rms

Deviation uncertainty	BW 6 Hz to 20 kHz	<1 % of reading + residual FM
------------------------------	-------------------	-------------------------------

Carrier frequency error		
Measurement range		-47 kHz to +47 kHz
Measurement uncertainty		≤2 kHz + drift of time base, see base unit specifications

AF generator

See specifications of R&S®CMU-B41 option audio generator/analyzer		
--	--	--

AF analyzer

See specifications of R&S®CMU-B41 option audio generator/analyzer		
--	--	--

CDMA2000® specifications – mobile station test

Standards	CDMA2000® standards CDMA2000® test standards	TIA/EIA IS-2000 Rev. 0 TIA/EIA IS-98-F
-----------	---	---

RF generator

Frequency range		
US/Korean Cellular (band class 0)	860.025 MHz to 893.985 MHz	
North American PCS (band class 1)	1930.000 MHz to 1990.000 MHz	
TACS band (band class 2)	917.0125 MHz to 959.9875 MHz	
JTACS band (band class 3)	832.0125 MHz to 869.9875 MHz	
Korean PCS (band class 4)	1840.000 MHz to 1870.000 MHz	
NMT-450 (band class 5)	421.675 MHz to 493.480 MHz	
IMT-2000 (band class 6)	2110.000 MHz to 2169.950 MHz	
North American 700 MHz Cellular band (band class 7)	746.000 MHz to 764.000 MHz	
1800 MHz band (band class 8)	1805.000 MHz to 1879.950 MHz	
900 MHz band (band class 9)	925.000 MHz to 958.750 MHz	
secondary 800 MHz band (band class 10)	851.000 MHz to 939.975 MHz	
400 MHz european PAMR (band class 11)	421.675 MHz to 493.475 MHz	
800 MHz PAMR band (band class 12)	915.0125 MHz to 920.9875 MHz	
2.5 GHz IMT-2000 extension (band class 13)	2620.000 MHz to 2690 MHz	
US PCS 1.9 GHz band (band class 14)	1930.000 MHz to 1995.000 MHz	
AWS band (band class 15)	2110.000 MHz to 2155.000 MHz	
US 2.5 GHz band (band class 16)	2624.000 MHz to 2690.000 MHz	
US 2.5 GHz forward link only band (band class 17)	2624.000 MHz to 2690.000 MHz	

Frequency resolution	channel spacing in line with standard	
----------------------	---------------------------------------	--

Frequency uncertainty		same as time base, see base unit specifications
-----------------------	--	--

Output level range	modulated signal	
RF 1	f < 2200 MHz	-120 dBm to -33 dBm
	f ≥ 2200 MHz	-120 dBm to -39 dBm
RF 2	f < 2200 MHz	-120 dBm to -16 dBm
	f ≥ 2200 MHz	-120 dBm to -22 dBm
RF 3 OUT	f < 2200 MHz	-99 dBm to +5 dBm
	f ≥ 2200 MHz	-99 dBm to -1 dBm

Output level resolution	modulated signal	0.1 dB
-------------------------	------------------	--------

Output level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	output level ≥ -108 dBm	
	f < 2200 MHz	<0.5 dB
	f ≥ 2200 MHz	<0.7 dB
RF 3 OUT	-80 dBm to +4 dBm	
	f < 2200 MHz	<0.7 dB
	f ≥ 2200 MHz	<0.9 dB

Output level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	output level ≥ -108 dBm	
	f < 2200 MHz	<0.7 dB
	f ≥ 2200 MHz	<1.5 dB
RF 3 OUT	-80 dBm to +4 dBm	
	f < 2200 MHz	<0.9 dB
	f ≥ 2200 MHz	<1.5 dB

Modulation		
Dual BPSK, multiple QPSK		1.2288 Mcps
AWGN		see AWGN generator
Carrier suppression		>35 dB
Waveform quality factor (ρ)		>0.985
Code channel level uncertainty	relative to the total CDMA output power F-PICH, F-PCH, F-FCH, F-SCH1, F-SCH2 all other channels	approx. 0.1 dB approx. 0.25 dB
Code channel resolution		0.1 dB
Code channel level range	relative to the total CDMA output power PICH, SYNC, FCH, SCH0, SCH1, PCH QPCH (relative to PICH level)	-20 dB to -1 dB -5 dB to +2 dB

AWGN generator		
Bandwidth		>1.8 MHz
Output level resolution		0.1 dB
Output level uncertainty	bandwidth 1.23 MHz	approx. 0.2 dB
Output level range	relative to total CDMA output power	-20 dB to +4 dB

Supported service options	in signaling mode	
Loopback service options		SO 2, 9, 55
Speech service options		SO 1, 3, 17, 0x8000
Test data service option		SO 32
Packet data service option		SO 33
Messaging tele service option		SO 6, 14

RF analyzer

Frequency range		
	US/Korean Cellular (band class 0)	815.025 MHz to 848.985 MHz
	North American PCS (band class 1)	1850.000 MHz to 1910.000 MHz
	TACS band (band class 2)	872.0125 MHz to 914.9875 MHz
	JTACS band (band class 3)	887.0125 MHz to 924.9875 MHz
	Korean PCS (band class 4)	1750.000 MHz to 1780.000 MHz
	NMT-450 (band class 5)	411.675 MHz to 483.480 MHz
	IMT-2000 (band class 6)	1920.000 MHz to 1979.950 MHz
	North American 700 MHz Cellular band (band class 7)	776.000 MHz to 794.000 MHz
	1800 MHz band (band class 8)	1710.000 MHz to 1784.950 MHz
	900 MHz band (band class 9)	880.000 MHz to 913.750 MHz
	secondary 800 MHz band (band class 10)	806.000 MHz to 900.975 MHz
	400 MHz european PAMR (band class 11)	411.675 MHz to 483.475 MHz
	800 MHz PAMR band (band class 12)	870.0125 MHz to 875.9875 MHz
	2.5 GHz IMT-2000 extension (band class 13)	2500.000 MHz to 2570.000 MHz
	US PCS 1.9 GHz band (band class 14)	1850.000 MHz to 1915.000 MHz
	AWS band (band class 15)	1710.000 MHz to 1755.000 MHz
	US 2.5 GHz band (band class 16)	2502.000 MHz to 2568.000 MHz

Measurement filter	in line with standard	bandwidth 1.23 MHz
---------------------------	-----------------------	--------------------

Frequency resolution	channel spacing in line with standard	
-----------------------------	---------------------------------------	--

Frequency uncertainty		same as time base, see base unit specifications
------------------------------	--	--

Power meter (frequency-selective)

Level range	HPSK, O-QPSK signal	
RF 1	f < 2200 MHz f ≥ 2200 MHz	-40 dBm to +44 dBm -34 dBm to +44 dBm
RF 2	f < 2200 MHz f ≥ 2200 MHz	-54 dBm to +30 dBm -48 dBm to +30 dBm
RF 4 IN	f < 2200 MHz f ≥ 2200 MHz	-80 dBm to -9 dBm -74 dBm to -9 dBm

Level uncertainty		
RF 1, RF 2, RF 4 IN	in temperature range +20 °C to +35 °C f < 2200 MHz f ≥ 2200 MHz	<0.5 dB <0.7 dB
	in temperature range +5 °C to +45 °C f < 2200 MHz f ≥ 2200 MHz	<0.7 dB <0.9 dB
Level resolution		0.1 dB

Modulation analyzer

Level range	HPSK, O-QPSK signal	
RF 1	f < 2200 MHz f ≥ 2200 MHz	-40 dBm to +44 dBm -34 dBm to +44 dBm
RF 2	f < 2200 MHz f ≥ 2200 MHz	-54 dBm to +30 dBm -48 dBm to +30 dBm
RF 4 IN	f < 2200 MHz f ≥ 2200 MHz	-80 dBm to -9 dBm -74 dBm to -9 dBm

RC1, RC2 (O-QPSK)	waveform quality, error vector magnitude, magnitude error, phase error	
ρ uncertainty	for ρ 0.9 to 1	<0.003
Frequency measurement range		-3 kHz to +3 kHz
Frequency measurement uncertainty	f < 2200 MHz f ≥ 2200 MHz	<10 Hz + drift of time base, <15 Hz + drift of time base, see base unit specifications

RC3, RC4 (HPSK)	waveform quality, error vector magnitude, magnitude error, phase error, channel power, code domain power, peak code domain error power,	
ρ uncertainty	for ρ 0.9 to 1	<0.003
Frequency measurement range		-3 kHz to +3 kHz
Frequency measurement uncertainty		<10 Hz + drift of time base, see base unit specifications
Relative measurement uncertainty	result >-33 dB	<0.1 dB

Measurements		
Modulation		overview EVM versus time, graphical ME versus time, graphical PE versus time, graphical I/Q analyzer
Power		standby/access-probe power open loop time response gated output power maximum output power minimum output power
Spectrum		
Code Domain Power		code domain power code domain error power channel power time/phase offset relative to pilot
Receiver		FER for FCH, SCH RLP/throughput statistics forward power control

R&S®CMU-B85 option speech codec

Speech decoder output	SPEECH HANDSET OUT	9-pin D-Sub connector
Output impedance		<10 Ω
Maximum output current		20 mA, peak
Full-range output level		1 V, peak

Speech coder input	SPEECH HANDSET IN	9-pin D-Sub connector
Input impedance		100 kΩ
Full-range input level	low sensitivity high sensitivity	1.4 V, peak 0.1 V, peak

1xEV-DO specifications – access terminal test

Standards	1xEV-DO standards 1xEV-DO test standards (access terminal)	TIA/EIA IS-856-2 TIA/EIA IS-866-A
-----------	---	--------------------------------------

RF generator

Frequency range	
US/Korean Cellular (band class 0)	860.025 MHz to 893.985 MHz
North American PCS (band class 1)	1930.000 MHz to 1990.000 MHz
Public Safety Bands (PSB)	772.000 MHz to 802.000 MHz
TACS band (band class 2)	917.0125 MHz to 959.9875 MHz
JTACS band (band class 3)	832.0125 MHz to 869.9875 MHz
Korean PCS (band class 4)	1840.000 MHz to 1870.000 MHz
NMT-450 (band class 5)	421.675 MHz to 493.480 MHz
IMT-2000 (band class 6)	2110.000 MHz to 2169.950 MHz
North American 700 MHz cellular band (band class 7)	746.000 MHz to 764.000 MHz
1800 MHz band (band class 8)	1805.000 MHz to 1879.950 MHz
900 MHz band (band class 9)	925.000 MHz to 958.750 MHz
secondary 800 MHz band (band class 10)	851.000 MHz to 939.975 MHz
400 MHz european PAMR (band class 11)	421.675 MHz to 493.475 MHz
800 MHz PAMR band (band class 12)	915.0125 MHz to 920.9875 MHz
2.5 GHz IMT-2000 extension (band class 13)	2620.000 MHz to 2690 MHz
US PCS 1.9 GHz band (band class 14)	1930.000 MHz to 1995.000 MHz
AWS band (band class 15)	2110.000 MHz to 2155.000 MHz
US 2.5 GHz band (band class 16)	2624.000 MHz to 2690.000 MHz
US 2.5 GHz forward link only band (band class 17)	2624.000 MHz to 2690.000 MHz

Frequency resolution	channel spacing in line with standard
----------------------	---------------------------------------

Frequency uncertainty	same as time base, see base unit specifications
-----------------------	--

Statistics	
Statistic count	1 to 1000
Values	current, average, min/max

Trigger	
Trigger sources	free run, internal, external, IF power, RF power
Trigger output	24-pin D-Sub connector AUX 3 super frame, power control frame, paging frame, sync frame, PP2S

Output level range	modulated signal	
RF 1	f < 2200 MHz f ≥ 2200 MHz	-120 dBm to -33 dBm -120 dBm to -39 dBm
RF 2	f < 2200 MHz f ≥ 2200 MHz	-120 dBm to -16 dBm -120 dBm to -22 dBm
RF 3 OUT	f < 2200 MHz f ≥ 2200 MHz	-99 dBm to +5 dBm -99 dBm to -1 dBm

Output level resolution	modulated signal	0.1 dB
-------------------------	------------------	--------

Output level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	output level ≥ -108 dBm $f < 2200$ MHz $f \geq 2200$ MHz	<0.5 dB <0.7 dB
RF 3 OUT	-80 dBm to +4 dBm $f < 2200$ MHz $f \geq 2200$ MHz	<0.7 dB <0.9 dB

Output level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	output level ≥ -108 dBm $f < 2200$ MHz $f \geq 2200$ MHz	<0.7 dB <1.5 dB
RF 3 OUT	-80 dBm to +4 dBm $f < 2200$ MHz $f \geq 2200$ MHz	<0.9 dB <1.5 dB

Modulation		
Dual BPSK		1.2288 Mcps
AWGN		see AWGN generator
Carrier suppression		>35 dB
Waveform quality factor (ρ)		>0.985
Code channel level uncertainty	relative to total 1xEV-DO output power	approx. 0.1 dB
Code channel resolution		0.1 dB
Code channel level range	relative to the total 1xEV-DO output power PICH, SYNC, FCH, SCH0, SCH1, PCH QPCH (relative to PICH level)	-20 dB to -1 dB -5 dB to +2 dB

AWGN generator		
Bandwidth		>1.8 MHz
Output level resolution		0.1 dB
Output level uncertainty	bandwidth 1.23 MHz	approx. 0.2 dB
Output level range	relative to total 1xEV-DO output power	-20 dB to +4 dB

Supported applications	in signaling mode	
Test applications		FTAP/RTAP, FETAP/RETAP
Default signaling application		
Default packet application		

RF analyzer

Frequency range	
US/Korean Cellular (band class 0)	815.025 MHz to 848.985 MHz
North American PCS (band class 1)	1850.000 MHz to 1910.000 MHz
Public Safety Bands (PSB)	742.000 MHz to 772.000 MHz
TACS band (band class 2)	872.0125 MHz to 914.9875 MHz
JTACS band (band class 3)	887.0125 MHz to 924.9875 MHz
Korean PCS (band class 4)	1750.000 MHz to 1780.000 MHz
NMT-450 (band class 5)	411.675 MHz to 483.480 MHz
IMT-2000 (band class 6)	1920.000 MHz to 1979.950 MHz
North American 700 MHz Cellular band (band class 7)	776.000 MHz to 794.000 MHz
1800 MHz band (band class 8)	1710.000 MHz to 1784.950 MHz
900 MHz band (band class 9)	880.000 MHz to 913.750 MHz
secondary 800 MHz band (band class 10)	806.000 MHz to 900.975 MHz
400 MHz european PAMR (band class 11)	411.675 MHz to 483.475 MHz
800 MHz PAMR band (band class 12)	870.0125 MHz to 875.9875 MHz
2.5 GHz IMT-2000 extension (band class 13)	2500.000 MHz to 2570.000 MHz
US PCS 1.9 GHz band (band class 14)	1850.000 MHz to 1915.000 MHz
AWS band (band class 15)	1710.000 MHz to 1755.000 MHz
US 2.5 GHz band (band class 16)	2502.000 MHz to 2568.000 MHz

Measurement filter	in line with standard	bandwidth 1.23 MHz
--------------------	-----------------------	--------------------

Frequency resolution	channel spacing in line with standard	
----------------------	---------------------------------------	--

Frequency uncertainty	same as time base, see base unit specifications
-----------------------	--

Statistics	
Statistic count	1 to 1000
Values	current, average, min/max

Trigger	
Trigger sources	free run, internal, external, IF power, RF power
Trigger output	24-pin D-Sub connector AUX 3 ControlSlot, ControlChannel, slot, PP2S

Power meter (frequency-selective)

Level range	modulated signal	
RF 1	f < 2200 MHz f ≥ 2200 MHz	-40 dBm to +44 dBm -34 dBm to +44 dBm
RF 2	f < 2200 MHz f ≥ 2200 MHz	-54 dBm to +30 dBm -48 dBm to +30 dBm
RF 4 IN	f < 2200 MHz f ≥ 2200 MHz	-80 dBm to -9 dBm -74 dBm to -9 dBm

Level uncertainty		
RF 1, RF 2, RF 4 IN	in temperature range +20 °C to +35 °C f < 2200 MHz f ≥ 2200 MHz	<0.5 dB <0.7 dB
	in temperature range +5 °C to +45 °C f < 2200 MHz f ≥ 2200 MHz	<0.7 dB <0.9 dB

Level resolution		0.1 dB
------------------	--	--------

Modulation analyzer

Level range	modulated signal	
RF 1	f < 2200 MHz f ≥ 2200 MHz	-40 dBm to +44 dBm -34 dBm to +44 dBm
RF 2	f < 2200 MHz f ≥ 2200 MHz	-54 dBm to +30 dBm -48 dBm to +30 dBm
RF 4 IN	f < 2200 MHz f ≥ 2200 MHz	-80 dBm to -9 dBm -74 dBm to -9 dBm

Waveform quality (ρ) uncertainty	for ρ 0.9 to 1	<0.003
Frequency measurement range		-3 kHz to +3 kHz
Frequency measurement uncertainty		<10 Hz + drift of time base, see base unit specifications
Relative measurement uncertainty	result >-33 dB	<0.1 dB

Measurements		
Modulation		overview EVM versus time, graphical ME versus time, graphical PE versus time, graphical I/Q analyzer
Power		
Spectrum		
Code domain power		code domain power code domain error power channel power
Receiver	in signaling mode	FTAP/RTAP, FETAP/RETAP

WCDMA specifications – mobile station (UE) test

Standard	3GPP FDD
Symbol rate	3.84 MHz

Synchronization output 2	BNC connector REF OUT 2
Frequency	30.72 MHz / n, n = 1 to 32

RF generator

Channels	non-signaling mode	
	P-CPICH, P-SCH, S-SCH, P-CCPCH, PICH, DPCCH, up to 4 HS-SCCHs, HS-PDSCH, E-AGCH, E-RGCH/E-HICH	
	OCNS R99 OCNS R5	16-channel orthogonal channel noise 6-channel orthogonal channel noise
	AWGN	bandwidth \geq 5.76 MHz
	reference measurement channels (RMC) in line with 3GPP TS 34.121	12.2 kbit/s, 64 kbit/s, 144 kbit/s, 384 kbit/s

Channels	signaling mode, codes selectable until conflict in code space occurs	
	P-CPICH, P-SCH, S-SCH, P-CCPCH, S-CCPCH, AICH, PICH, up to 4 HS-SCCHs, HS-PDSCH	
	OCNS R99 OCNS R5	16-channel orthogonal channel noise 6-channel orthogonal channel noise
	AWGN	bandwidth \geq 5.76 MHz
	DPCH signaling radio bearer (SRB)	1.7 kbit/s, 2.5 kbit/s, 3.4 kbit/s, 13.6 kbit/s
	DPCH reference measurement channels (RMC) in line with 3GPP TS 34.121 DL and UL DL/UL BTFD	12.2 kbit/s, 64 kbit/s, 144 kbit/s, 384 kbit/s 144 kbit/s / 64 kbit/s, 384 kbit/s / 64 kbit/s, 384 kbit/s / 144 kbit/s 1.95 kbit/s, 4.75 kbit/s, 5.15 kbit/s, 5.9 kbit/s, 6.7 kbit/s, 7.4 kbit/s, 7.95 kbit/s 10.2 kbit/s, 12.2 kbit/s
	DPCH voice (echo or speech codec)	4.75 kbit/s, 5.15 kbit/s, 5.9 kbit/s, 6.7 kbit/s, 7.4 kbit/s, 7.95 kbit/s 10.2 kbit/s, 12.2 kbit/s

Frequency range	non-signaling mode	
		869 MHz to 894 MHz 925 MHz to 960 MHz 1805 MHz to 1880 MHz 1930 MHz to 1990 MHz 2110 MHz to 2170 MHz 2620 MHz to 2690 MHz

Frequency range	signaling mode	
	band 1 band 2 band 3 band 4 band 5 band 6 band 7 band 8 band 9	2110 MHz to 2170 MHz 1930 MHz to 1990 MHz 1805 MHz to 1880 MHz 2110 MHz to 2155 MHz 869 MHz to 894 MHz 875 MHz to 885 MHz 2620 MHz to 2690 MHz 925 MHz to 960 MHz 1844.9 MHz to 1874.9 MHz

Frequency offset	-100 kHz to +100 kHz
-------------------------	----------------------

Frequency resolution	0.1 Hz
-----------------------------	--------

Frequency setting	by channel number or frequency
--------------------------	--------------------------------

Output level range	
RF 1	-120 dBm to -37 dBm
RF 2	-120 dBm to -20 dBm
RF 3 OUT	-100 dBm to 0 dBm

Output level resolution	manual mode	0.1 dB
	remote mode	0.01 dB

Output level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	output level \geq -120 dBm f < 2200 MHz f \geq 2200 MHz	<0.6 dB <0.8 dB
RF 3 OUT	output level \geq -80 dBm f < 2200 MHz f \geq 2200 MHz	<0.8 dB <1.0 dB

Output level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2	output level \geq -120 dBm f < 2200 MHz f \geq 2200 MHz	<0.9 dB <1.5 dB
RF 3 OUT	output level \geq -80 dBm f < 2200 MHz f \geq 2200 MHz	<1.0 dB <1.5dB

Output level setting	setting reference	relative to CPICH or total output power
-----------------------------	-------------------	---

Channel levels	non-signaling mode	
	P-CPICH, P-SCH, S-SCH, P-CCPCH, PICH, DPCCH, OCNS, HS-SCCH, HS-PDSCH, E-AGCH, E-RGCH/E-HICH	-30 dB to +15 dB relative to CPICH

Channel levels	signaling mode	
	P-CPICH, P-SCH, S-SCH, P-CCPCH, S-CCPCH, PICH, AICH, DPCH, OCNS, HS-SCCH, HS-PDSCH	-30 dB to +15 dB relative to CPICH

Signal quality		
Error vector magnitude (EVM)	global EVM for DL RMC in line with 3GPP TS 34.121 C3.1 to C3.4 with DPCH/CPICH = 0 dB	<8 %, rms

Signal quality	16QAM	
Error vector magnitude (EVM)	global EVM for 16QAM reference setup: 3GPP TS34.121 FRC H-Set3 for 16 QAM	<8 %, rms

R&S®CMU-B96 additional RF generator option

Path 2 for WCDMA

Standard	3GPP FDD	
Frequency range	non-signaling mode	
		869 MHz to 894 MHz 925 MHz to 960 MHz 1805 MHz to 1880 MHz 1930 MHz to 1990 MHz 2110 MHz to 2170 MHz
Frequency range	WCDMA signaling mode	
	band 1 band 2 band 3 band 4 band 5 band 6 band 8 band 9	2110 MHz to 2170 MHz 1930 MHz to 1990 MHz 1805 MHz to 1880 MHz 2110 MHz to 2170 MHz 869 MHz to 894 MHz 875 MHz to 885 MHz 925 MHz to 960 MHz 1844.9 MHz to 1874.9 MHz
Frequency resolution	2.5 kHz	
Frequency uncertainty	same as time base, see base unit specifications	
Error vector magnitude (EVM)	global EVM for DL RMC in line with 3GPP TS 34.121 C3.1 to C3.4 with DPCH/CPICH = 0 dB	<8 %, rms
Output level range		
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-115 dBm to -82 dBm -103 dBm to -70 dBm
RF 2		-103 dBm to -70 dBm
Output level resolution	RF1 and RF2	0.1 dB
Output level range	overrange mode	
RF 1	without R&S®CMU-U99 with R&S®CMU-U99	-110 dBm to -38 dBm -90 dBm to -24 dBm
RF 2		-90 dBm to -24 dBm
RF 3 OUT		-70 dBm to -1 dBm
Output level resolution	for overrange mode	1 dB
Influence on RF interface		
Reduced input level range	if R&S®CMU-B96 is installed	
RF 1	continuous input power	max. 2 W
RF level uncertainty	the usage of R&S®CMU-B96 in overrange mode may influence all RF signal levels and quality	

RF analyzer (TX measurements)

Frequency range	non-signaling mode	
		824 MHz to 849 MHz 880 MHz to 915 MHz 1710 MHz to 1785 MHz 1850 MHz to 1910 MHz 1920 MHz to 1980 MHz 2500 MHz to 2570 MHz

Frequency range	signaling mode	
	band 1 band 2 band 3 band 4 band 5 band 6 band 7 band 8 band 9	1920 MHz to 1980 MHz 1850 MHz to 1910 MHz 1710 MHz to 1785 MHz 1710 MHz to 1755 MHz 824 MHz to 849 MHz 830 MHz to 840 MHz 2500 MHz to 2570 MHz 880 MHz to 915 MHz 1749.9 MHz to 1784.9 MHz

Frequency offset		-100 kHz to +100 kHz
-------------------------	--	----------------------

Frequency resolution		1 Hz
-----------------------------	--	------

Frequency setting		by channel number or frequency
--------------------------	--	--------------------------------

Level setting		by autoranging or manual mode
----------------------	--	-------------------------------

Max. level setting range		
RF 1	peak envelope power ⁴ (PEP)	-38 dBm to +53 dBm
RF 2	peak envelope power ⁴ (PEP)	-52 dBm to +39 dBm
RF 4 IN	peak envelope power (PEP)	-77 dBm to +0 dBm

Statistics		
Statistic count		1 to 1000
Values		current, average, min/max

Trigger	non-signaling mode	
Trigger sources		free run, internal, external, IF power, slot, frame, TPC, HSDPCCH, auto
Trigger input	15-pin D-Sub connector AUX 3 pin 8	external
Trigger slot delay		0 to 14 slots
Trigger delay offset		-10239 to + 10239 × 1/4 chip
Trigger output	15-pin D-Sub connector AUX 3 pin 2 to 5	frame, slot, TPC, HSDPCCH

Trigger	signaling mode	
Trigger sources		free run, external, slot, frame, signaling, IF power, TPC, preamble, PRACH-MSG part, compressed mode, change of TFC, HSDPCCH, auto
Trigger input	15-pin D-Sub connector AUX 3 pin 8	external
Trigger slot delay		0 to 14 slots
Trigger delay offset		-10239 to + 10239 × 1/4 chip
Trigger output	15-pin D-Sub connector AUX 3 pin 2 to 4 15-pin D-Sub connector AUX 3 pin 5, depending on signaling state and trigger source	frame, slot, TPC preamble, PRACH-MSG part, compressed mode, change of TFC, HSDPCCH

Modulation analysis

Measurement filter	receiver filter in line with standard	3.84 MHz, RRC, $\alpha = 0.22$
---------------------------	---------------------------------------	--------------------------------

Analysis modes	QPSK, WCDMA uplink
-----------------------	--------------------

Input level range		
RF 1	continuous power ³ peak envelope power ⁴ (PEP)	-21 dBm to +47 dBm -16 dBm to +53 dBm
RF 2	continuous power peak envelope power ⁴ (PEP)	-35 dBm to +33 dBm -30 dBm to +39 dBm
RF 4 IN	continuous power and PEP	-50 dBm to 0 dBm

Error vector magnitude (EVM)		
Measurement range		up to 25%
Applications	non-signaling mode	overview EVM versus time, graphical ME versus time, graphical PE versus time, graphical I/Q analyzer
Measured parameters		error vector magnitude magnitude error phase error I/Q origin offset I/Q imbalance peak code domain error waveform quality
Inherent EVM	<i>RF Attenuation → Low Noise</i> <i>RF Attenuation → Low Noise</i> , with R&S®CMU-Z6 calibration and $f < 2200$ MHz <i>RF Attenuation → Low Noise</i> , with R&S®CMU-Z6 calibration and $f \geq 2200$ MHz	<2.5 %, rms <1.5 %, rms <2.5 %, rms
Resolution		0.1%
Measurement length	QPSK mode WCDMA mode	1 timeslot (2560 chips) 1/4 timeslot (640 chips) 1 timeslot
Marker	in graphical menus	reference , Abs1, Abs2, D-line

Frequency error		
Measurement range		±3 kHz
Uncertainty	$f < 2200$ MHz and max. value of 10 slots $f \geq 2200$ MHz and average value of 10 slots	<10 Hz + drift of time base, <10 Hz + drift of time base, see base unit specifications
Resolution		1 Hz

I/Q offset		
Inherent I/Q offset		<-55 dB
Resolution		0.01 dB

I/Q imbalance		
Inherent I/Q imbalance		<-30 dB
Resolution		0.01 dB

Peak code domain error (PCDE)		
Inherent PCDE	for SF = 4	<-40 dB
Resolution		0.01 dB

I/Q analyzer	non-signaling mode	
Display	QPSK mode and WCDMA mode waveform type zoom rotation measurement length	graphical display constellation diagram, vector diagram, eye diagram I, Q, I/Q 1, 2, 5, 10, 20 0°, 45° 1 timeslot (2560 chips), 1/4 timeslot (640 chips)

Spectrum measurements

Reference level for full dynamic range		
RF 1	rms peak envelope power ⁴ (PEP)	+14 dBm to +47 dBm up to +53 dBm
RF 2	rms peak envelope power ⁴ (PEP)	+0 dBm to +33 dBm up to +39 dBm
RF 4 IN	rms peak envelope power (PEP)	-18 dBm to 0 dBm up to 0 dBm

Adjacent channel leakage ratio (ACLR filter application)		
Measurement filter	receiver filter in line with standard	3.84 MHz, RRC, $\alpha = 0.22$
Display		bar graphs of rms and peak values, numerical values rms and peak of current, average and max. values
Frequency offsets	first adjacent channel second adjacent channel	±5 MHz ±10 MHz
Uncertainty	for -33 dBc first adjacent channel level for -43 dBc second adjacent channel level	<0.5 dB <0.5 dB
Dynamic range (<i>High dynamic mode → On</i>)	first adjacent channel second adjacent channel	>54 dB >64 dB
Resolution		0.1 dB
Measurement length		1 timeslot (2560 chips) 1/2 timeslot (1280 chips) 1/4 timeslot (640 chips) 1/8 timeslot (320 chips)

Adjacent channel leakage ratio (ACLR FFT/OBW application)		
Measurement filter	receiver filter in line with standard	3.84 MHz, RRC, $\alpha = 0.22$
Display		continuous spectrum with 25 MHz bandwidth, numerical values rms and peak of current, average and max. values
Frequency offsets	first adjacent channel second adjacent channel	±5 MHz ±10 MHz
Resolution bandwidth		20 kHz, 3.84 MHz
Dynamic range (<i>High dynamic mode → On</i>)	first adjacent channel second adjacent channel	>54 dB >64 dB
Occupied bandwidth	measurement range	1 MHz to 6 MHz
	measurement uncertainty	<50 kHz
	measurement resolution	20 kHz
Measurement length		≥1 timeslot (2560 chips) ≥1/2 timeslot (1280 chips) ≥1/4 timeslot (640 chips) ≥1/8 timeslot (320 chips)

Spectrum emission mask (SEM application)		
Measurement filter	receiver filter in line with standard	3.84 MHz, RRC, $\alpha = 0.22$
Display		graphical and numerical values of current, average and max values

Resolution bandwidth	frequency offset 2.5 MHz to 3.5 MHz 3.5 MHz to 7.5 MHz 7.5 MHz to 8.5 MHz 8.5 MHz to 12.5 MHz	30 kHz 1 MHz 1 MHz 1 MHz
Measurement interval		≥1 timeslot (2560 chips) ≥1/2 timeslot (1280 chips) ≥1/4 timeslot (640 chips) ≥1/8 timeslot (320 chips)

Power meter (frequency-selective)⁷

Measurement applications	maximum power, minimum power off power power versus slot inner loop power	bandwidth approx. 7 MHz 3.84 MHz, RRC, $\alpha = 0.22$ bandwidth approx. 7 MHz 3.84 MHz, RRC, $\alpha = 0.22$
---------------------------------	--	--

Power versus slot	measurement width step width step count step delay	0.25, 0.5, 1 slot 1 slot to 30 slots 1 to 100 0 to 100
--------------------------	---	---

Level range		
RF 1	continuous power ³ peak envelope power ⁴ (PEP)	-52 dBm to +47 dBm -42 dBm to +53 dBm
RF 2	continuous power peak envelope power ⁴ (PEP)	-66 dBm to +33 dBm -56 dBm to +39 dBm
RF 4 IN	continuous power ⁸ peak envelope power (PEP)	-89 dBm to 0 dBm -79 dBm to 0 dBm

Level uncertainty	in temperature range +20 °C to +35 °C	
RF 1	-10 dBm to +47 dBm, rms $f < 2200 \text{ MHz}$ $f \geq 2200 \text{ MHz}$ -44 dBm to -10 dBm, rms $f < 2200 \text{ MHz}$ $f \geq 2200 \text{ MHz}$	<0.5 dB <0.7 dB <0.7 dB <0.9 dB
RF 2	-24 dBm to +33 dBm, rms $f < 2200 \text{ MHz}$ $f \geq 2200 \text{ MHz}$ -60 dBm to -24 dBm, rms $f < 2200 \text{ MHz}$ $f \geq 2200 \text{ MHz}$	<0.5 dB <0.7 dB <0.7 dB <0.9 dB
RF 4 IN	-24 dBm to 0 dBm, rms $f < 2200 \text{ MHz}$ $f \geq 2200 \text{ MHz}$ -85 dBm to -24 dBm, rms $f < 2200 \text{ MHz}$ -83 dBm to -24 dBm, rms $f \geq 2200 \text{ MHz}$	<0.5 dB <0.7 dB <0.7 dB <0.9 dB

⁷ The specified data is valid for *RF Attenuation* set to *Low Noise*.

⁸ Upper limit depends on crest factor.

Level uncertainty	in temperature range +5 °C to +45 °C	
RF 1	-10 dBm to +47 dBm, rms f < 2200 MHz f ≥ 2200 MHz -44 dBm to -10 dBm, rms f < 2200 MHz f ≥ 2200 MHz	<0.7 dB <0.9 dB <0.9 dB <1.1 dB
RF 2	-24 dBm to +33 dBm, rms f < 2200 MHz f ≥ 2200 MHz -60 dBm to -24 dBm, rms f < 2200 MHz f ≥ 2200 MHz	<0.7 dB <0.9 dB <0.9 dB <1.1 dB
RF 4 IN	-24 dBm to 0 dBm, rms f < 2200 MHz f ≥ 2200 MHz -85 dBm to -24 dBm, rms f < 2200 MHz -83 dBm to -24 dBm, rms f ≥ 2200 MHz	<0.7 dB <0.9 dB <0.9 dB <1.1 dB

Level resolution	0.01 dB
-------------------------	---------

Code domain power⁷

Measurement filter	receiver filter in line with standard	3.84 MHz, RRC, $\alpha = 0.22$
---------------------------	---------------------------------------	--------------------------------

Display modes	CDP/code auto CDP/code manual CDP/code Rho auto CDP/code Rho manual
----------------------	--

Spreading Factor (SF)	auto mode manual setting	4, 8, 16, 32, 64, 128, 256
------------------------------	-----------------------------	----------------------------

Level range	
RF 1	-8 dBm to +47 dBm
RF 2	-22 dBm to +33 dBm
RF 4 IN	-45 dBm to 0 dBm

Level uncertainty	<0.5 dB
--------------------------	---------

Level resolution	0.01 dB
-------------------------	---------

Receiver quality (bit error rate measurements)

Measurement types	BER, BLER, DBLER, FDR
Measurement method	loopback mode 2, loopback mode 1 with RLC transparent
Number of transport blocks	1 to 50000
DL/UL transport block size	symmetric, asymmetric
DL/UL timing	876 chips to 1172 chips

R&S®CMU-B52 option speech codec

Speech decoder output	SPEECH HANDSET OUT	9-pin D-Sub connector
Output impedance		<10 Ω
Maximum output current		20 mA, peak
Full-range output level		1 V, peak

Speech coder input	SPEECH HANDSET IN	9-pin D-Sub connector
Input impedance		100 kΩ
Full-range input level	low sensitivity high sensitivity	1.4 V, peak 0.1 V, peak

Bluetooth® specifications

Standards		Bluetooth® Core Specifications Version 1.1
-----------	--	---

RF generator

RF channel definition		2402 MHz + k × 1 MHz, k = 0 to 93
-----------------------	--	-----------------------------------

Frequency range		2402 MHz to 2495 MHz
-----------------	--	----------------------

Frequency resolution	channel spacing in line with standard	1 MHz
----------------------	---------------------------------------	-------

Frequency offset range		±500 kHz
------------------------	--	----------

Frequency offset resolution		1 kHz
-----------------------------	--	-------

Frequency uncertainty		±1 Hz + drift of time base, see base unit specifications
-----------------------	--	---

Hopping scheme	modes in line with standard	Europe (except France), USA
		France
		RX/TX single frequency
		Reduced hopping

Output level range	modulated signal	
RF 1		-106 dBm to -33 dBm
RF 2		-106 dBm to -12 dBm
RF 3 OUT		-90 dBm to +5 dBm

Output level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2		<0.9 dB
RF 3 OUT		<1.1 dB

Output level uncertainty	in temperature range +5 °C to +45 °C	
RF 1, RF 2		<1.6 dB
RF 3 OUT		<1.6 dB

Output level resolution		0.1 dB
-------------------------	--	--------

Modulation		
GFSK	AC coupling cut-off frequency 100 Hz	1 Mbps, B × T = 0.5
Modulation index	11110000 pattern, frequency deviation 160 kHz	0.32
Modulation index range	frequency deviation 100 kHz to 220 kHz	0.20 to 0.44
Modulation index resolution		0.01
Modulation index uncertainty	11110000 pattern, frequency deviation 160 kHz	±5 %

RF analyzer

RF channel definition	2402 MHz + k × 1 MHz, k = 0 to 93	
Frequency range	2402 MHz to 2495 MHz	
Frequency resolution	channel spacing in line with standard	1 MHz
Frequency uncertainty		±1 Hz + drift of time base, see base unit specifications
Hopping scheme	modes in line with standard	Europe (except France), USA France RX/TX single frequency reduced hopping

Power meter (frequency-selective) and power versus time

Measurement bandwidth	filter definition: passband	
	<i>Filter Bandwidth → wide</i>	2.0 MHz
	<i>Filter Bandwidth → narrow</i>	1.3 MHz
Reference level for full dynamic range	GFSK signal	
RF 1		0 dBm to +41 dBm
RF 2		-14 dBm to +33 dBm
RF 4 IN		-32 dBm to 0 dBm
Dynamic range	<i>Filter Bandwidth → wide</i>	>55 dB, rms
Level uncertainty	in temperature range +20 °C to +35 °C	
RF 1, RF 2	from full scale setting down to -25 dB	<0.7 dB
RF 4 IN	from full scale setting down to -25 dB	<0.9 dB
Level uncertainty	in temperature range +5 °C to +45 °C	
RF1, RF2	from full scale setting down to -25 dB	<1.0 dB
RF4IN	from full scale setting down to -25 dB	<1.1 dB
Level resolution	in manual mode	0.1 dB
	in remote control mode	0.01 dB

Modulation analyzer

Measurement bandwidth	filter definition: passband	
	<i>Filter Bandwidth → wide</i>	2.0 MHz
	<i>Filter Bandwidth → narrow</i>	1.3 MHz
Level range	GFSK signal	
RF 1, RF 2, RF 4 IN		from full scale setting down to -25 dB
Total measurement range for frequency offset and frequency deviation		-250 kHz to +250 kHz
Frequency offset uncertainty in preamble	for deviation ≤ 160 kHz	≤ 2 kHz
Frequency deviation uncertainty in payload	for 100 kHz < deviation ≤ 200 kHz	
	11110000 pattern	≤ 2 %
	10101010 pattern	≤ 4 %

Frequency drift uncertainty	measured in burst related to frequency offset value in preamble	
	10101010 pattern	
	maximum	≤ 2 kHz
	typically	≤ 1 kHz

Frequency resolution	in manual mode	1 kHz
	in remote control mode	1 Hz

Timing measurement

Range		± 20 μ s
Resolution		≤ 0.25 μ s
Uncertainty		≤ 0.25 μ s + resolution

R&S®CMU-B52 option speech codec

Speech decoder output	SPEECH HANDSET OUT	9-pin D-Sub connector
Output impedance		< 10 Ω
Maximum output current		20 mA, peak
Full-range output level		1 V, peak

Speech coder input	SPEECH HANDSET IN	9-pin D-Sub connector
Input impedance		100 k Ω
Full-range input level	low sensitivity	1.4 V, peak
	high sensitivity	0.1 V, peak

R&S®CMU-B17 option I/Q/IF interface

I/Q interface

Analog I/Q outputs	IF → I/Q; TX and RX paths, analog I/Q output	connector I/Q CH1
I/Q bandwidth		0 MHz to 2.5 MHz
Max. output voltage range	EMF	-1 V to +1 V, peak $\sqrt{I^2 + Q^2} = 1 \text{ V, peak}$
Output impedance		50 Ω
I and Q amplitude imbalance		<2 %
for WCDMA function group		<2.5 %
Offset voltage	in temperature range +20 °C to +35 °C	<4 mV
	in temperature range +20 °C to +35 °C for WCDMA function group	<5 mV
	in temperature range +5 °C to +45 °C	<8 mV

Analog I/Q inputs	I/Q → IF; TX-path, analog I/Q input	connector I/Q CH1
I/Q bandwidth		0 MHz to 2.5 MHz
Max. input voltage range		-0.5 V to +0.5 V, peak $\sqrt{I^2 + Q^2} = 0.5 \text{ V, peak}$
Input impedance		50 Ω
Carrier suppression	in temperature range +20 °C to +35 °C	>40 dB
	in temperature range +5 °C to +45 °C	>35 dB
Sideband suppression	$f_{I/Q} < 1 \text{ MHz}$	>45 dB
	$1 \text{ MHz} < f_{I/Q} < 2.5 \text{ MHz}$	>40 dB

Analog I/Q inputs	I/Q → IF; RX path, analog I/Q input	connector I/Q CH1
I/Q bandwidth		0 MHz to 2.5 MHz
Max. input voltage range		-0.5 V to +0.5 V, peak $\sqrt{I^2 + Q^2} = 0.5 \text{ V, peak}$
Input impedance		50 Ω
Carrier suppression	in temperature range +20 °C to +35 °C	>35 dB ⁹
	in temperature range +5 °C to +45 °C	>35 dB ⁹
Sideband suppression	$f_{I/Q} < 1 \text{ MHz}$	>45 dB
	$1 \text{ MHz} < f_{I/Q} < 2.5 \text{ MHz}$	>40 dB

Influence on RF interface

GSM/EDGE measurements		
Additional influence on signal quality	analog I/Q input and output considered; for TX and RX paths	
Phase error	GMSK	<3°, peak <1°, rms
EVM	8PSK	<5 %, rms

WCDMA measurements	3GPP FDD, UE test	
Additional influence on signal quality	analog I/Q input and output considered; for TX and RX paths	
EVM		<5 %, rms

RF level uncertainty	bypass with I/Q IF OUT, I/Q IN/OUT, IF IN/OUT	
Output level uncertainty	at RF 1, RF 2, RF 3 OUT	add 0.3 dB to R&S®CMU200 base unit specifications
Input level uncertainty of frequency-selective power meter	at RF 1, RF 2, RF 4 IN	add 0.3 dB to R&S®CMU200 base unit specifications

⁹ For GSMK modulation and max. input voltage at I/Q inputs.

IF interface

IF inputs, TX path		connector IF3 TX CH1 IN
IF level range		up to -5 dBm, PEP
Standard IF frequencies	RF/GSM (GMSK and 8PSK)/ TDMA/CDMA2000® WCDMA	13.85 MHz 15.36 MHz
IF inputs, RX path		connector IF3 RX CH1 IN
IF level range		up to +2 dBm, PEP
Standard IF frequencies	RF/GSM (GMSK and 8PSK)/ TDMA/CDMA2000® WCDMA	10.7 MHz 7.68 MHz
IF outputs, TX path		connector IF3 TX CH1 OUT
IF level range		up to -5 dBm, PEP
Standard IF frequencies	RF/GSM (GMSK and 8PSK)/ TDMA/CDMA2000® WCDMA	13.85 MHz 15.36 MHz
IF outputs, RX path		connector IF3 RX CH1 OUT
IF level range		up to +6 dBm, PEP
Standard IF frequencies	RF/GSM (GMSK and 8PSK)/ TDMA/CDMA2000® WCDMA	10.7 MHz 7.68 MHz

Remarks

- Due to the modulation schemes used Bluetooth and AMPS standards will not be supported.
- The options R&S®CMU-B17 and R&S®CMU-B73 use the same mainboard connector of the R&S®CMU200. Therefore either the R&S®CMU-B17 or the R&S®CMU-B73 can be ordered for a single instrument.

Additional information for GSM:

To avoid influences on the fading profile, the following is highly recommended:

- To set all timeslots to the same level.
- To use for the TX signal of the R&S®CMU200 the same RF frequencies and RF levels for both TCH and BCCH.
- To switch hopping off.

Aspects to be considered if TX or RX signal paths are interrupted:

The RF frequency of the R&S®CMU200 influences the rotating direction of the I/Q vector. The direction is inverted for $f < 1200.1$ MHz; this can be compensated for by changing I and Q.

R&S®CMU200 generator or analyzer RF frequency		
	100 kHz to 1200.0999999 MHz	1200.1 MHz to 2700.0 MHz
R&S®CMU200 I/Q output vector	inverted rotation swap I output with Q output for proper operation	normal rotation
R&S®CMU200 I/Q input vector	inverted rotation swap I input with Q input for proper operation	normal rotation

The rotating direction must be considered if the R&S®CMU200 signal path from the link handler board to the frontend and vice versa is interrupted, i.e. if the signal is not returned to the same R&S®CMU200 block after external handling.

Examples:

- The rotating direction must **not** be taken into account if the transmitted signal is routed from the I/Q output of the R&S®CMU-B17 to an external fading simulator and then returned to the R&S®CMU200 I/Q input (the R&S®CMU200 in combination with the Fading Simulator R&S®ABFS or R&S®SMIQ/SMIQB14, the R&S®CMU200 providing the faded RF signal).
- The rotating direction must be considered if the transmitted signal is forwarded to an external fading simulator and is not returned to the I/Q input of the R&S®CMU200 (the R&S®CMU200 in combination with the R&S®SMIQ, the R&S®SMIQ providing the faded RF signal).

Notes for measuring I/Q/IF signals applied to inputs of the R&S®CMU-B17 option on the R&S®CMU200 RX path:

- The RF spectrum analyzer function (RF function group) cannot be used.
- The displayed RF power levels are not related directly to the applied I/Q/IF voltages. The analyzer settings of the R&S®CMU200 RF interface (RF 1, RF 2, RF 4 IN) have to be considered additionally (*Analyzer Level → RF Max. Level*).
- I/Q inputs have a fixed attenuation of 2 dB; e.g. the RF power meter readout for an applied 500 mV I/Q peak voltage will be 2 dB below the value set in *RF Max. Level*.
- IF inputs do not have a fixed attenuation. The max. IF input level is 2 dBm. The RF power meter readout for the mentioned max. IF signal level (2 dBm) will be 2 dB below the value set in *RF Max. Level*.
- We recommend switching off the autoranging function.
- RF and IF trigger functions are not possible.
- The WCDMA RF compensation filter is switched off (I/Q IN/OUT, IF IN/OUT, IFIN_I/Q IN/OUT).
- WCDMA UE test: ACLR/SEM measurement is not applicable.

R&S®CMU-B41 option audio generator/analyzer

AF generator

Output impedance	<4 Ω
Maximum output current	20 mA, peak
AF sine generator	
Frequency range	20 Hz to 20 kHz
Frequency uncertainty	same as time base + half resolution, see base unit specifications
Frequency resolution	0.1 Hz
Output level range	10 µV to 5 V
Output level resolution	at level <10 mV at level ≥10 mV
	10 µV 0.1 %
Output level uncertainty	at level ≥1 mV and frequency ≤10 kHz
THD+N ¹⁰	≤1.5 % + resolution
THD ¹⁰	at level ≥100 mV into load ≥600 Ω at level ≥100 mV into load ≥600 Ω
	≤0.05 % ≤0.025 %

AF analyzer

Input impedance	1 MΩ 100 pF
AF voltmeter	
Frequency range	50 Hz to 20 kHz
Level range	50 µV to 30 V
Level resolution	at level <1 mV at level ≥1 mV
	1 µV 0.1 %
Level uncertainty	at 1 mV ≤ level ≤ 2 V at 2 V < level ≤ 20 V
	<1 % + resolution <2 % + resolution

THD+N meter	
Measurement bandwidth	21 kHz
Frequency range	100 Hz to 10 kHz
Level range	10 mV to 30 V
Resolution	0.01 % THD+N
Inherent distortion	at 100 mV ≤ level ≤ 20 V
Uncertainty	<0.05 % THD+N at 100 mV ≤ level ≤ 2 V at 2 V < level ≤ 20 V
	<1 % + inherent resolution <2 % + inherent resolution

R&S®CMU-U99/B99 option RF1 level range identical to RF2

With the R&S®CMU-U99/B99 option installed, the input/output level range and the input/output level uncertainty for RF 1 are the same as for RF 2.

With the R&S®CMU-U99/B99 option installed, the VSWR of the RF generator and analyzer at RF 1 is as follows:

VSWR	RF generator and RF analyzer	
RF1	10 MHz to 2000 MHz	<1.2
	2000 MHz to 2200 MHz	<1.4
	2200 MHz to 2700 MHz	<1.6

¹⁰ Measurement bandwidth 21.9 kHz

The specifications for the R&S®CMU200 (Order No. 1100.0008.02/10/30/53) refer to a fully equipped unit with all relevant options installed.

Specifications are valid under the following conditions:

Data without tolerance limits is not binding.

In compliance with the 3GPP/3GPP2 standard, chip rates are specified in Mcps (million chips per second), whereas bit rates and symbol rates are specified in kbps (thousand bits per second) or ksps (thousand symbols per second).

Mcps, kbps and ksps are not SI units.

For more general information about the R&S®CMU200 please refer to the product brochure PD 0758.0039.12, version ≥07.00.



For product brochure, see PD 0758.0039.12
and www.rohde-schwarz.com
(search term: CMU200)



www.rohde-schwarz.com

Europe: +49 1805 12 4242, customersupport@rohde-schwarz.com
USA and Canada: 1-888-837-8772, customer.support@rsa.rohde-schwarz.com
Asia: +65 65 130 488, customersupport.asia@rohde-schwarz.com